

STEICO *durelisdek*

enhanced floor deck protection

Flooring Systems
naturally made from timber



PEEL-CLEAN OR PERMANENT SURFACE SEAL



STEICO *durelisdek* is the brand new deck option for house builders, developers and suppliers offering enhanced protection during the construction period. When used with STEICO *joists* STEICO *durelisdek* can help avoid issues such as movement and noisy floors.

Features unique triple protection which minimises the risk and extent of board swelling and subsequent movement which can contribute to issues and noise within the floor structure after completion or hand over of the property.

STEICO is the only company whose distributors offer the complete floor unit both I Joists and decking in one package together with all fixing accessories ensuring the very highest floor performance and assured quality.

- High quality Durelis board with "Top Surface" technology inhibiting moisture ingress
- Environmentally friendly uses up to 80 % recycled wood
- Easy remove slip resistant peel off film for excellent site protection
- Wax surface sealer under the film
- Fully customised fixing kit
- Also available with a permanent acrylic surface sealer
- The complete floor solution with STEICO *joists*
- FSC® certified
- Tongued and Grooved all four edges
- Produced in the EU to STEICO's specification

For more information please visit our website at www.steico.co.uk



STEICOdurelisdek BOARD SPECIFICATIONS

Thickness [mm]	Board Coverage [mm]	Weight [kg / m ²]	Pieces per pallet	Pallet Coverage [m ²]	Pallet weight [kg]
18	2400 x 600	12.5	100	144.0	ca. 1800
22	2400 x 600	15.6	80	115.2	ca. 1800

STEICOdurelisdek TECHNICAL VALUES

Baseboard conforms to	EN 312
Edge profile	tongue & groove four edges
Board density [kg/m ³]	ca. 685
Formaldehyde class E1	≤ 8 mg / 100 g
Raw material	wood fibre, resin, hardener, wax, polyethylene film, bonding agent

STEICOdurelisdek PRODUCT DESCRIPTION

STEICOdurelisdek is an enhanced triple protected moisture resistant chipboard flooring product designed for temporary exposure to the weather during the construction period and offers additional protection against site spoil. By constructing the deck prior to the building becoming weather tight a safe working platform is provided and other trades can work safely beneath.

The Durelis base board has unique "Top Surface" technology giving very dense and enhanced moisture resistant surface layers thereby inhibiting moisture ingress and subsequent swelling risks. The board is also moisture resistant throughout.

The top of the board is also coated with a high performance wax surface sealer for further durability in exposed situations even if the peel off surface film has been damaged and allows for easy cleaning at the end of the construction period for a pristine finish.

The surface of the Peel Clean board is covered with a distinct blue, durable and water proof peel off film that is both UV resistant and anti slip. The film stays in place until all construction work is complete and the building water tight and can then be easily peeled off to leave a clean floor prior to hand-over. The durability of the board and coatings means when properly installed the deck can remain exposed to the elements for up to 42 days.

STEICO supplies all the deck fixing accessories including a D4 adhesive for bonding the boards to the joists and the boards to each other sealing the joints when cured. A high quality edge sealing tape is also offered to improve protection. STEICOdurelisdek is also available with a high performance permanent surface sealer rather than a peel-off.

STEICO is Europe's largest manufacturer of I Joists and supplies many of the leading house builders in the UK. The addition of a premium enhanced decking available with the Joists offers



The mark of responsible forestry



STRUCTURAL
TIMBER ASSOCIATION
Building solutions in timber

STEICO
engineered by nature

Your STEICO Agent

www.steico.co.uk